

SS-1122

SmartSoda.



Efficient, highly reliable, and just the right capacity specifications as a work horse unit; the SS-1122 is a fully mechanical Hot, Cold, and Ambient Dispenser with an LG Compressor and a 2 Gallon Cold Tank.

Featuring a redesigned new to market dual function mechanical paddle, the SS-1122 is able to dispense both hot and ambient water from a single spigot, allowing for the classic mechanical 2 spigot / paddle design while being able to deliver 3 temperatures of water.

SPECIFICATIONS & FEATURES

Dimensions	14" W x 14" L x 48" H
Weight	54 lbs
Cold Tank	2 gallons
Hot Tank	1 gallon
Cooling Rate	3 gal/hour 37-50°F
Heating Rate	2.8 gal/hour 180°F

LG Compressor
Anti-Microbial Panels
Hot & Cold Water
Hot Water Safety Lock

Hot Power Consumption 1000W
Cold Power Consumption 100W
110V~127V AC / 50-60Hz
Refrigerant R134A
Climate Class T
USA Final Assembly & Quality Control

2-STAGE FILTRATION

Stage 1: Sediment
Stage 2: Post Carbon Filter

3-STAGE FILTRATION

Stage 1: Sediment
Stage 2: Pre-Carbon
Stage 3: Post Carbon Filter

4-STAGE ULTRAFILTRATION

Stage 1: Sediment
Stage 2: Pre-Carbon Filter
Stage 3: Ultra-Filtration Membrane
Stage 4: Post Carbon Filter

REVERSE OSMOSIS PURIFICATION

Stage 1: Sediment Filter
Stage 2: Activated Carbon Filter
Stage 3: 100 GDP Reverse Osmosis Membrane
Stage 4: Post Carbon Filter

AVAILABLE IN:



White



Black

